



## Ward Care Solutions

### Marut Engineering Electronics

NorthBlock: 123, West End Mall, Next to Hotel Hilton,  
Janakpuri East, New Delhi. Office: No. 4, Navrattan Appt., BH.  
Time Square, dwarka, Nashik-422005. Works: M-100/12,  
Ambad, MIDC, Nasik-422010. Ph.: 0253-6603310

Email: [marutengg@gmail.com](mailto:marutengg@gmail.com)

Website: [www.bigmachines.co.in](http://www.bigmachines.co.in) Our Associates: @Rama

Bricks@Saipore Concrete Technologies

Youtube link: <https://youtu.be/VNTIVLiGccA>

## BX2000



### Features

Bx2000 Plus has facility to raise the back section

This section is operated by a crank mechanism provided at the foot end of the bed

The raising section allow the nursing staff to change positions for various activities and clinical positions with relative ease

Pre-treated and powder coated finish

Supplied in SKD condition

- **BX4000**



### Features

- Bx4000 Plus has facility to raise the back and upper leg sections
- These sections are operated by crank mechanisms provided at the foot end of the bed

- The raising sections allow the nursing staff to change positions for various activities and clinical positions with relative ease
- Pre-treated and powder coated finish
- Supplied in SKD condition

## Bx 1003 ATTENDANT BED CUM CHAIR



### Overall Approx Dimension

Dimension from End to End - 1850 mm x 785 mm, 73" x 31" (L x W)

Platform Dimension (without Armrest) - 1850 mm x 625 mm 73" x 25" L x W

- Fixed Height - 525 mm H (without Upholstery)
- Upholstery Height - 75 mm H

### Features

- Back Rest Angle of 65 degrees
- Manual Adjustment for back section and leg section
- Manual Chair Position
- Two Armrest pivoted with backrest on each side
- Tray at bottom
- All MS Parts are pre-treated and powder coated
- Load Bearing Capacity of 120 kgs
- Supplied in KDC.
  - Supplied in KDC.

### Ax1009 Deluxe Bedside Locker



#### FEATURES

- Approx dimension: 400 mm square x 820 mm H.
- Locker made from machine pressed CRCA steel sheets enclosed on three sides.
- Having one box and one drawer, fitted with membrane top with raised edges, drawer front and cabinet door.
- Mounted on four swivel synthetic body castors, 50 mm wheel diameter without brake.
- Buffers at rear.
- Pre-treated and powder coated finish.

### Ax1016 Deluxe Adjustable Bedside Table



- Approximate dimension: Top 810 mm L x 352 mm W.
- Two sectional laminated top with railing on fixed section. Raised edge on one side on tiltable section.
- Aluminum extruded telescopic section fitted with gas spring for height adjustable from approx 760 mm to 1050 mm.
- Mild steel rectangular tubular base frame mounted on four swivel synthetic body castors, 50 mm wheel diameter without brake.
- Pre-treated and powder coated finish.

### Ax006 Wardcare Bedside Locker - NH S. S



#### Approximate

- dimension: 400 mm square x 820 mm H
- Locker made from machine pressed CRCA steel sheets enclosed on three side having one box and one drawer with slide.
- Fitted with superimposed stainless steel top with raised edge on three sides.
- Mounted on four swivel, synthetic body castors, 50 mm wheel diameter without brake
- Buffers at rear.
- Pre-treated and powder coated finish.

### Ax1001 Wardcare Bedside Locker (S.S. Top)



- **FEATURES**
- Approximate dimension: 400 mm square x 820 mm H
- Machine pressed CRCA steel sheet locker box with door.
- Fitted with superimposed stainless steel top raised edges on three sides.
- Mild steel tubular legs fitted with rubber feet.
- Pre-treated and powder coated finish.
- Supplied in KDC.

### [Ax1011 Wardcare Overbed Table](#)



#### FEATURES

Overall approximate dimension: 1120 mm L x 450 mm W x 965 mm H.

Laminated top of 760 mm L x 450 mm W.

Mild steel rectangular tubular base frame mounted on four swivel synthetic body castors 50 mm diameter without brake.

Pre-treated and powder coated finish.

Supplied in KDC.

### [Ax1012 Adjustable Bedside Table](#)



#### FEATURES

Approximate top dimension of 810 mm L X 352 mm W.

- Two section laminated top.
- M.S. tubular telescopic stem, with geared S.S. handle for height adjustable from approximately 760 mm to 1050 mm.
- M.S. rectangular tubular base frame mounted on four twin wheel non rusting castors, 50 mm diameter without brake.
- Pre-treated and powder coated.
- Supplied in KDC.

### [Ax1014 Folding Food Table \(S.S.\)](#)



#### FEATURES

Approximate top dimension of 810 mm L X 352 mm W.

Two section laminated top.

- M.S. tubular telescopic stem, with geared S.S. handle for height adjustable from approximately 760 mm to 1050 mm.
- M.S. rectangular tubular base frame mounted on four twin wheel non rusting castors, 50 mm diameter without brake.
- Pre-treated and powder coated.
- Supplied in KDC.

### [1021 - Steel Stool \(Fully Powder Coated\)](#)



- Overall approximate dimension: 300 mm x 300 mm x 510 mm, 12 x 12 x 20 (Lx W x H)
- Framework of mild steel, pressed bent angles and ORCA steel sheet top
- Legs fitted with rubber feet
- Pre-treated and powder coated finish

### [1603 - Single Step Stool](#)



- Approximate height: 230 mm, 9"

- Approximate step dimension: 510 mm x 300 mm, 20" x 12" (Lx W)
- Mild steel tubular frame
- Mild steel top fitted with aluminium tread flats
- Legs fitted with rubber feet
- Pre-treated and powder coated finish



1604 - Double Step Stool

- Approximate height: 230/450 mm, 9/18"
- Approximate step dimension: 510 mm x 300 mm, 20" x 12" (Lx W)
- Mild steel tubular frame
- Mild steel top fitted with aluminium tread flats
- Leg fitted with rubber feet
- Pre-treated and powder coated finish



1038 - Commode Chair 1

- Overall approximate dimension: 520 mm x 520 mm x 880 mm, 20 x 20 x 35" (W x D x H)
- Cushion and S.S. bowl
- S.S. tubular construction
- 125 mm diameter synthetic body castors, two with brake and two without brake
- Supplied in KDC



1043A - Stainless Steel Saline Stand (Tubular Base)

- Strong stainless steel tubular construction mounted on five pronged rectangular tubular base
- Fitted with five swivel, rust proof, synthetic body castors 50 mm (2") wheel diameter without brake
- Stainless steel rod with double hooks
- Height adjustable from approximate 1620 mm to 2340 mm (64" to 92")



Specifications (Bx l000)

- Overall Approximate Dimension: 2090 mm x 910 mm x 600 mm (L x W x H) — (82" x 36" x 24")
- Bed Frame Dimension: 1980 mm x 910 mm (LxW)—(78" x 36")
- Mattress Dimension: 1980mmx910mm (LxW)

#### Specifications (Bx l000B)

- Overall Approximate Dimension: 1940 mm x 838 mm x 600 mm (LxWx H) - (75" x 33")
- Bed Frame Dimension : 1830 mm x 838 mm (L x W) - (72" x 33")
- Mattress Dimension: 1830 mm x 838 mm (Lx W)
- Pre-treated and powder coated finish.
- Sockets provided for Mosquito Net Poles

#### Optional Accessories

- Mattress Arrestor (set of two) (01 71)
- Single mattress with 4" thick PU Foam of 40 density covered with PVC Rexine (0111)
- Single mattress with 3" thick PU Foam of 32 density covered with PVC Rexine (01 1 1 C)
- Single mattress with 4" thick PU Foam of 32 density covered with PVC Rexine (01 1 1 E)
- Telescopic I.V. Pole with suitable bracket (0154)
- Mosquito Net Poles (set offour) (0157)

- Side Railings (0253)

### Bx2000 Basic Bed



- The Basic back adjustable bed has facility to raise the back section
- This section is operated by a crank mechanism provided at the foot end of the bed
- The raising section allow the nursing staff to change positions for various activities and clinical positions with relative ease
- Pre-treated and power coated finish
- Supplied in SKD condition

\*Above beds are available with Polymer Moulded Handle



### **BS MX 10**

**SEMI MOTORIZED ICU BED ADVENT**  
Size: 2250mm x 1050mm x 520mm - 620mm ht

- Five function Semi Motorized ICU bed.
- 4 Section top detachable in 18 swg CRCA sheet.
- Easily detachable polymer Head and Foot end bows.
- 4 Pcs Polymer Railings.
- 125 mm Diagonally locking Castors.
- Wired remote control all the movements.
- Optional provided with Nurse control Panel.
- Manul CPR from both sides of the bed.
- CPR function/ Zero Position can be attained from the remote.

- Under Bed lighting Optional.
- Back light Hand set so that c an be easily operated in darkens.
- I.V. position at all the four corners of the Bed.
- Bed can be provided with Molded ABS top.
- Bed available with regular back rest with X ray permeable section.



### **BS MX 11**

**SEMI MOTORIZED ICU BED EXCEL**  
Size: 2250mm x 965mm x 485mm - 710mm ht

- Five function Semi Motorized ICU bed.
- 4 Section top in 18 swg CRCA sheet.
- Easily detachable polymer Head and Foot end bows.
- Aluminum Railings knock down type.
- 125 mm Diagonally locking Castors.
- Wired remote control all the movements.
- Back light Hand set so that c an be easily operated in darkens.
- I.V. position at all the four corners of the Bed.
- Bed can be provided with Molded ABS top.
- Bed available with regular back rest with X ray permeable section.



### **BS 400**

**MANUAL FOWLER BED ADVENT**  
Size: 2250mm x 1050mm x 550mm ht

- Two function Manual Fowler bed.
- 4 Section top in 18 swg CRCA sheet.
- Easily detachable polymer Head and Foot end bows.
- 4 Pcs Polymer Railings.

- 125 mm Diagonally locking Castors.
- Wall deflection buffers at all the four corners of the bed.
- All positions attained with help of heavy screw mechanisms.
- I.V. position at all the four corners of the Bed.
- The leggings made from 40 mmx 40mm square tube with nylon feet.
- The bed frame made from 60 x 30mm Rectangular ERW Tube.
- Bed can be provided with Molded ABS top.
- Bed available with regular back rest with X ray permeable section.



#### BS 401

**MANUAL FOWLER BED EXCEL (R)**  
Size: 2055mm x900mm x550mm ht

- Two function Manual Folwer bed.
- 4 Section top in 18 swg CRCA sheet.
- Easily detachable polymer Head and Foot end bows.
- Collapsible Aluminum railings.
- 125 mm Diagonally locking Castors.
- Urine Hooks on either side of the bed.
- All positions attained with help of heavy screw mechanisms.
- I.V. position at all the four corners of the Bed.
- The leggings made from 40mmx 40mm square tube with nylon feet.
- The bed frame made from 60 x 30mm Rectangular ERW Tube.
- Bed can be provided with Molded ABS top.
- Bed available with regular back rest with X ray permeable section.



#### BS 501

**MANUAL SEMI FOWLER BED EXCEL (R)**  
Size: 2055mm x900mm x550mm ht

- Single function Manual Semi Fowler bed.
- 4 Section top in 18 swg CRCA sheet.
- Easily detachable polymer Head and Foot end bows.
- Collapsible Aluminum railings.
- 125 mm Diagonally locking Castors.
- Back rest position attained with help of heavy screw mechanisms.
- Urine hooks on either side of the bed.
- I.V. position at all the four corners of the Bed.
- The leggings made from 40 mmx 40mm square tube with nylon feet.
- The bed frame made from 60 x 30mm Rectangular ERW Tube.
- Bed can be provided with Molded ABS top.
- Bed available with regular back rest with X ray permeable section.



#### BS 602

**ATTENDANT BED WITH CUSHION**  
Size: 1800mm x610mm x380mm ht

- Attendant bed with built in cushion.
- Complete with built in Cushion 75mm.
- Top frame made from 50 x 25mm ERW tube.
- Legs 30mm x 30 mm ERW tube with nylon feet.
- 3 horizontal supports.



#### BS 603



### ATTENDANT CHAIR/BED

Size: 1800mm x610mm x380mm ht

- Attendant bed which becomes a chair folded.
- 3 Section top complete with built in Cushion.
- Easily retractable sections.
- Hind wheels to move the chair/ bed easily.
- Space saver.



BS 393

### REVOLVING STOOL CUSHION TOP

Size : 290 dia. X 425-675mm

- Tubular Steel Structure with Cushion Top. Height adjustable from 425 to 675 mm with the help of smooth screw mechanism. Pretreated & Epoxy Powder Coated.

Optionally available fully Stainless Steel.



BS 5111

### BED SIDE SCREEN 4 FOLD

Size: 1675 mm HT x 2440 mm

- Tubular structure 25.4mm dia 1.25 mm thick tube.
- Four section provided with Screen cloth.
- 50 mm dia revolving wheels.
- Two Different models
  - a) Complete stainless steel
  - b) Complete M.S. Powder coated.



BS 511

### BED SIDE SCREEN

Size: 1675 mm HT x 2440 mm

- Tubular structure 25.4mm dia 1.25 mm thick tube.
- Three section provided with Screen cloth.
- 50 mm dia revolving wheels.
- Two Different models
  - a) Complete stainless steel
  - b) Complete M.S. Powder coated.



BS 311

### CYLINDER TROLLEY

- Tubular structure 25.4mm dia 1.25 mm thick tube.
- Legs fitted with nylon feet with Metal inserts
- 100 mm dia revolving wheels
- Two Different models
  - a) Complete stainless steel
  - b) Complete M.S. Powder coated.



BS 681

### UTILITY STOOL

Size: 405mm X 405X 455mm ht.

- Tubular structure 25.4 x 25.4 x 1.25 mm thick tube.
- Legs fitted with nylon feet with Metal inserts



- Top made form 1.25 mm Thick CRCA/S.S Sheet with 3mm thick frame
- Three Different models
  - a) Complete stainless steel
  - b) Powder coated base with Stainless steel top.



**BS 591**

**DOUBLE STEP STOOL**

Size: 610mm X 455X 455mm ht.

- Tubular structure 25.4mm X25.4mm 1.25 mm thick tube.
- Legs fitted with nylon feet with Metal inserts
- Top made form 1.25 mm Thick CRCA/S.S Sheet with aluminum treads
- Two Different models
  - a) Complete stainless steel
  - b) Complete M.S. Powder coated.



**BS 590**

**SINGLE STEP STOOL**

Size: 610mm X 455X 305mm ht.

- Tubular structure 25.4mm dia 1.25 mm thick tube.
- Legs fitted with nylon feet with Metal inserts
- Top made form 1.25 mm Thick CRCA/S.S Sheet
- Two Different models
  - a) Complete stainless steel
  - b) Complete M.S. Powder coated.



**BS 131**

**FRESH & SOILED LENIN TROLLEY.**  
Size: 460 x 1090 x 8910 mm. Ht.

- Rectangular trolley complete stainless steel 304 Grade.
- Shelves made from 1 mm thick S.S 304 Grade.
- Railings on three side of each shelf and top ( 12mm dia. S,S tube)
- Vertical Section 25.4 x 25.4mm S.S tube. 1.25 mm thick.
- 100 mm dia non rusting castors.
- Lenin trolley with horizontal supports in 12mm dia S.S tube with bag



**BS 383**

**BS**

**OVER BED TABLE STOOL TYPE.**

Size: 610 x 900 x 610 mm. Ht.

- Tubular structure base made form 16 mm dia ERW tube.
- Light weight can be placed under the bed when not in use.
- Top membrane with ply sides rounded.
- Also available in S.S structure with Membrane top.



**BS 381**

**OVER BED TABLE PUSH TYPE.**

Size: 1115 x 455 x 965 mm. Ht.

- Tubular structure made form 25.4mm dia 16 swg tube

- Top membrane with ply.
- top flush fitting with open ends rounded off.
- Horizontal Section 20mm dia tube. 1.25 mm thick.
- 75 mm dia revolving castors.

**Models:**

**Stainless Steel frame with membrane top.**

**Complete Stainless steel.**

**Powder coated with Membrane top.**

**BS 245**



**RECT. STAINLESS**

**STEEL BED SIDE TROLLEY.**

**Size: 430 x 300 x 760 mm. Ht.**

- Rectangular trolley with 2 shelves and top complete stainless steel
- Shelves and top made from 1 mm thick S.S 304 grade
- Railings on three side of each shelf and top ( 8mm dia. S,S bar)
- Vertical Section 20 x 20mm S.S tube. 1.25 mm thick.
- 50 mm dia non rusting PU castors.



**BS 246**

**SQ. STAINLESS STEEL BED SIDE TROLLEY**

**Size: 380 x 380 x 760 mm. Ht.**

- Rectangular trolley with 2 shelves and top complete stainless steel
- Shelves and top made from 1 mm thick S.S 304 grade
- Railings on three side of each shelf ( 8mm dia. S,S bar)
- Top having 3 sides raised by 50mm.
- Vertical Section 20 x 20mm S.S tube. 1.25 mm thick.

- 50 mm dia non rusting PU castors.



**BS 243**

**BED SIDE LOCKER**

**Size: 355 x 380 x 760 mmHt.**

- Locker 3 sides enclosed with double press bent door
- Louvers on either side for ventilation
- Top in 304 grade Stainless steel having 3 sides raised
- Locker and Top mounted on ERW tube 20x 20 mm x 1.25 mm thick
- inbuilt door handle completely press bent evildoing handle protrusions
- Pre treated and Epoxy powder coated.
- Also available in complete 304 grade Stainless steel.



**BS 242**

**BED SIDE LOCKER EXECUTIVE**

**Size: 380 x 380 x 820 mmHt.**

- Locker 3 sides enclosed, with drawer on telescopic channels.
- Louvers on either side for ventilation
- Top in 304 grade Stainless steel having 3 sides raised
- Provided 50 mm PU castors.
- Nylon Buffers provided on the hind side of the locker.
- Pre treated and Epoxy powder coated.
- Also available in complete 304 grade Stainless steel.



**BS 241**

**BED SIDE LOCKER EXCEL**

Size: 385 x 390 x 760 mmHt.

- Locker 3 sides enclosed, with drawer on telescopic channels.
- Louvers on either side for ventilation.
- Top, Drawer front & Door for cabinet made form good quality Ply.
- with membrane with rounded edges to avoid damages.
- Doors fitted with hinges made from High strength Engineering Plastic.
- Provided 50 mm PU castors.
- Nylon Buffers provided on the hind side of the locker.
- Pre treated and Epoxy powder coated.



**BS 240**

**BED SIDE LOCKER EXCEL WITH OVER BED TABLE**

Size: 630 x 390 x 900 mm.Ht.

- Locker 3 sides enclosed, with drawer on telescopic channels.
- Louvers on either side for ventilation.
- Top, Drawer front & Door for cabinet made form good quality Ply.
- with membrane with rounded edges to avoid damages.
- Doors fitted with hinges made from High strength Engineering Plastic.
- Provided 75 mm PU castors.
- Nylon Buffers provided on the hind side of the locker.
- Bottle holder in S.S 304 grade provided.
- Provided with File/ Document container.
- Height adjustable, Fold able over bed table with membrane top.

- Over bed table with Quick release spring Mechanism.
- Size of over bed table 695 x 380 mm.



**BS 705**

**DROP SIDE BABY BED POPULAR**

Size: 1370mm x825mm x560mm ht

- Baby bed uniformly perforated.
- 2 Section top in 18 swg CRCA sheet.
- Powder coated fixed type Head and Foot end bows.
- Telescopic full length railings
- Urine hooks on either side of the bed
- I.V. position at all the four corners of the Bed.
- The leggings made from 40 mmx 40mm square tube with nylon feet.
- The bed frame made from 60 x 30mm Rectangular ERW Tube.



**BS 210**

**INVALID WHEEL CHAIR**

Size: 660mm x 1115mm x 915mm ht

- Complete chair Stainless steel 304 grade
- Wheels with self propelling hand hoops
- Foldable foot rest in Aluminum.
- 200 mm dia front revolving heavy duty castors.
- Seat & Back in S.S sheet 304 grade 18 swg thick.
- Fixed arm is high strength engineering plastic.
- Weight carrying capacity 150 kgs.
- Optionally available in M.S Powder coated. with cushion Seat back.



### BS 211

#### INVALID WHEEL CHAIR EXCEL

Size: 660mm x 1115mm x 915mm ht

- Complete chair Stainless steel 304 grade
- Wheels with self propelling hand hoops
- Foldable foot rest in Aluminum.
- 200 mm dia front revolving heavy duty castors.
- Molded Cushion seat and back.
- Fixed arm is high strength engineering plastic.
- Weight carrying capacity 150 kgs.
- Optionally available in M.S Powder coated. with cushion Seat back.



### BS 209

#### FOLDING WHEEL CHAIR

Size: 940mm x 230mm x 890mm ht

- Complete chair Chrome plated
- Wheels with self propelling hand hoops
- Foldable foot rest in P.P
- 200 mm dia front revolving heavy duty castors.
- Braked provided for locking of side wheels.
- Back and seat in durable high strength
- Fixed arm rest rubberized.
- Weight carrying capacity 100 kgs.



### BS 212

#### COMMODE CHAIR

Size: 520mm x 520mm x880mm ht

- Complete chair Stainless steel 304 grade
- 125 mm dia revolving heavy duty castors.
- Detachable Seat in FRP .
- Removable side arm rest.
- Stainless steel bowl.
- Optional Removable Cushion top

#### Bed Accessories Solutions



### BS B2

#### PARTIAL BOWS

Size: According to the bed

- Bed bow having a partial panel in high strength Engineering plastic P.P
- Fits exactly as the regular Ms. or S.S Bows
- Useful when bed width is below 900 mm and conventional bows do not fit because of the width this matched the same elegance and look.



### BS B3

#### MEMBRANE PANEL BOWS

Size: According to the bed

- Bed bow having a partial membrane panels
- Fits exactly as the regular Ms. or S.S Bows
- Useful when bed width is below 900 mm and conventional bows do not fit because of the width this matched the same elegance and look.



#### BS R5

**2 PCS BED SIDE RAILINGS EXTRA LONG**  
Size: 1020 mm x260 mm

- Bed Railings in P.P
- 2 pcs occidental type with inclination indicators.
- Fits to the bed side



#### BS B1

**BOWS**  
Size: 950 mm x 530 mm

- bed bow made in high strength Engineering plastic P.P
- Pin type fitting which gives more strength.
- Easily detachable and can be locked with locks provided



**4 PCS BED SIDE RAILINGS**  
Size: 720mm x300 mm

- Bed Railings in P.P
- 4 pcs occidental type
- Fits to the back rest and the foot end panel.



#### BS S1

**TELESCOPIC IV ATTACHMENT**  
Size: 1080 mm l

- Tubular structure form 20mm dia 1.25 mm thick tube
- 12 mm dia internal tube with 4 poles
- Available in M.S Epoxy powder coated/ 304 grade S.S
- 



#### BS R2

**SLIDE DOWN BED SIDE RAILS**  
Size: 1500mm l x 400 mm ht.

- Telescopic Vertical bed side rails.
- 8 vertical members, with Sliding Members in 304 grade S.S bar.
- Locking with help f of knobs.
- Detachable can be installed to any Hospital bed with rectangular side tube.
- Available is MS epoxy Powder coated/ Stainless steel



#### BS R1

**COLLAPSIBLE BED SIDE RAILS**  
Size: 1480 mm l x 365mm ht

- Collapsible bed side rails made from Aluminum Alloy.

- 6 vertical members.
- Spring loaded locking mechanism.
- complete railing is anodized.

- **OT SOLUTIONS**



**BS 661**

**SURGICAL INSTRUMENT CABINET**  
 Size: 1980 mm HT x 480 mm X 910 mm wide

- Compact cabinet made from 0.8 mm thick CRCA sheet.
- Provided with 4 shelves adjustable..
- Front door with full length glass with embedded handles
- Complete body is oven baked & Doors are powder coated



**BS 671**

**INSTRUMENT CABINET**  
 Size: 1600 mm HT x 445 mm X 635 mm wide

- Compact cabinet made from 1 mm thick CRCA sheet.
- Provided with 5 adjustable glass shelves.
- Front door and 2 sides with full length glass.
- Complete Tubular structure Epoxy powder coated.



**BS 151**

**OPERATION TABLE HEIGHT ADJUSTABLE**  
 Size: 1830mm x510mm x735-860mm ht

- Height adjustable Operation table.
- 3 section top with foot end easily detachable.
- Top frame made from 50 x 25mm ERW tube.
- Positions of Height , Trendelenburg & Reverse trendelenburg.
- Back rest adjustable on Ratchets to provide a Chair position.
- Provided with step stool, Pair of Arm rest, Lithotomy bars with belt.
- IV Provision along IV attachment provided.
- 50 mm thick cushion provided.

Also available in completely Stainless Steel.



**BS 152**

**OPERATION TABLE SCREW TYPE**  
 Size: 1830mm x510mm x735-810mm ht

- Fixed Height Operation table.
- 3 section top with foot end easily detachable.
- Top frame made from 50 x 25mm ERW tube.
- Positions of Trendelenburg & Reverse trendelenburg.
- Back rest adjustable on Ratchets to provide a Chair position.
- Provided with step stool, Pair of Arm rest, Lithotomy bars with belt.
- IV Provision along IV attachment provided.
- 50 mm thick cushion provided.

Also available in completely Stainless Steel.



**BS 512**



### SWAB RACK

Size: 1675 mm HT x 800 mm

- Tubular structure 25.4mm dia 1.25 mm thick tube.
- Single section provided with 48 hooks.
- 100 mm dia revolving wheels.
- complete 304 grade S.S

- Complete Powder coated.
- Legs made form 30 mm x30mm x 1.25mm thick tube.
- 450 mm head flap adjustable on ratchets.
- Top made from 1.25 mm thick CRCA sheet.
- Optional provided with 50 mm mattress.
- Also available in complete stainless steel.

### EXAM ROOM SOLUTIONS



### BS 141 REGULAR

#### EXAMINATION COUCH REGULAR

Size: 1830 x 610 x 7600 mmHt.

- Complete Powder coated.
- 75 mm thick built in Mattress with in buit pillow.
- Frame made form 50 mm x25mm x 1.25mm thick tube.
- S.S. legs provided to avoid rusting of legs because of moping.
- Tuck away type Single Step stool with Aluminum treads.
- 4 cupboards with lock , single drawer and single writing pad.
- Optionally available with gas spring assisted head rest and 3 compartments.



### BS 142

#### EXAMINATION TABLE GYNAEC

Size: 1830 x 610 x 7600 mmHt.



### BS 143

#### EXAMINATION TABLE

Size: 1830 x 610 x 7600 mmHt.

- Complete Powder coated.
- Legs made form 30 mm x30mm x 1.25mm thick tube.
- 450 mm head flap adjustable on ratchets.
- Top made from 1.25 mm thick CRCA sheet.
- Optional provided with 50 mm mattress.
- Also available in complete stainless steel.

- **TRANSFER SOLUTIONS**



### BS 346



### TRANSFER TROLLEY SYSTEM

Size: 2130mm x 610mm x 810mm ht

- Stretcher Top transferable on tow different under carriages.
- Top rolls over on either trolleys with help of Nylon rollers
- Provided with locking mechanism once top crosses over.
- Top made from 18 swg CRCA sheet with tubular 25.4mm dia ERW tube.
- 200 mm diagonally locking castors plate Type.
- Pre-treated & Epoxy Powder Coated.
- Optionally available is Complete Stainless Steel 304 Grade.
- Optionally available with Cylinder cage, medicine tray and Railings.



### BS 345

#### STRETCHER ON TROLLEY

Size: 2130mm x 610mm x 810mm ht

- Stretcher On Trolley.
- Single section detachable top.
- Top made from 18 swg CRCA sheet with tubular 25.4mm dia ERW tube.
- 200 mm diagonally locking castors plate Type.
- Pre-treated & Epoxy Powder Coated.
- Optionally available is Complete Stainless Steel 304 Grade.
- Optionally available with Cylinder cage, medicine tray and Railings.



### BS 344

### FOLDING TYPE STRETCHER TROLLEY

Size: 2130mm x 610mm x 810mm ht

- Folding Type Stretcher Trolley.
- 3 Section top.
- 125 mm Diagonally locking Castors
- Pre-treated & Epoxy Powder Coated.
- Optionally available is Complete Stainless Steel 304 Grade.
- Optionally available with 150 mm/200 mm dia revolving castors.



### BS 342

#### MANUAL TRAUMA CARE RECOVERY TROLLEY

Size: 2130mm x 610mm x 610mm - 810mm ht

- Four function Manual Recovery Trolley.
- 2 Section top in X ray Permaible High Pressure laminate.
- Collapsible S.S .
- 125 mm Diagonally locking Castors.
- Height adjustable with help of Heavy Duty Screw Mechanism.
- I.V. position at all the corner of the trolley.
- Cylinder Cage attached
- 50 mm thick mattress.
- Screw mechanism assisted back rest TB & RTB.



### BS 341

#### RECOVERY TROLLEY EXCEL

Size: 1920mm x 650mm x 525mm - 810mm ht

- **Four function Manual Recovery Trolley.**
- **2 Section top in P.P.**
- **Collapsible P.P Railings.**
- **125 mm Diagonally locking Castors.**
- **All positions attend with help of heavy screw mechanisms.**
- **I.V. position at all the corner of the trolley.**
- **Cylinder Cage attached**
- **25 mm thick mattress.**
- **Gas spring assisted back rest.**

### **Waiting Area Solutions**



#### **BS W3**

#### **WAITING CHAIRS POPULAR**

- **Multi seats chair**
- **Perforated sheet seat and back.**
- **Provided with or without side handles.**
- **Detachable Chrome plated legs.**
- **Models Single seat/ 2 seats/ 3seats/ 4seats.**
- **color options Black.**



#### **BS W1**

#### **WAITING CHAIRS EXCELL**

- **Three seats chair 36 kg weight**
- **Perforated sheet**
- **Provided with or without cushion**
- **Chrome plated legs and side handles**
- **Models Single seat/ 2 seats/ 3seats/ 4seats.**
- **color options Grey/ Metallic Silver/ Black.**